This home has dramatic views to the arroyo and light spills into the living spaces throughout the home. Upon entering the home, the kitchen, living, and dining rooms flow freely between one another creating an expansive space filled with abundant light. The basement contains the master bedroom and bath, offering complete privacy from the living spaces above. The master bedroom has its own private patio spilling out into the Santa Fe landscape.

Vallarta

UNIT K - TOTAL HEATED SQUARE FOOTAGE - 1,850

2 Bedrooms - 2 Baths

Open Concept Kitchen, Living and Dining Areas

9' Ceilings

Single Car Finished Garage

Custom Front Door Design by Legorreta


Walled Garden Patio and Upstairs Balcony

Separate Laundry Room





Second Floor



Vallarta

UNIT K

TOTAL HEATED SF – 1,850

FLOOR PLANS ARE SUBJECT TO CHANGE.
VERIFY WITH YOUR ZOCALO REPRESENTATIVE.

First Floor

BASE FEATURES

Tile in public areas - entry, dining room, living room, kitchen

Carpeted stairs and bedrooms

Semi-custom cabinetry in kitchen, baths and laundry room

Porcelain tile counter tops in kitchen and baths

Wood-burning fireplace

Numerous skylights

Pre-wiring for alarm, some speaker locations

Wired for high speed internet access

Master bath soaking tub and stand-alone shower

Recessed lighting

"Master Cool" evaporative cooling In-floor radiant hot water heating

GE appliances

CONSTRUCTION

Foundation: Concrete foundation walls, concrete floor slabs

Exterior Wall Construction: 2x6 wood stud walls at 16" on center with wood O.S.B. sheathing

Interior Wall Construction: 2x4 wood stud walls at 16" on center

Unit Separation walls: Double 2x4 wood stud wall with 1 and 2-hour fire resistive construction

STC sound rating 55-60

Wood Floor Construction: Wood Floor Joists (Truss Joist Silent Floor) at 16" on center Topping Slab at Wood Floor Construction: 1/14"thick"Therma-Floor"topping slab

Roof Construction: Engineered Pre-fabricated wood trusses at 24" on center with built-in roof slope

Insulation: Kraft paper-faced batt insulation R=19 at walls, R+30 at roof

Roofing: 3-ply built-up roof with granular surfaced cap sheet

Stucco: 2-coat cementious stucco with textured and painted elastomeric paint

Garage: Batt insulation and gypsum board wall finish at framed walls and ceiling cavities

WINDOWS & DOORS

Entry Door: Custom made 3'-0"x 7"6" - designed by Legorreta +Legorreta

Interior Doors: Flush birch solid-core wood doors with solid wood rabbeted frames

Garage Door: Flush panel insulated steel door

Windows and patio doors: Semco extruded aluminum-clad wood windows, dual-pane clear insulating glass

SKYLIGHTS

Curb-mounted double dome skylights with white over clear plastic cover and aluminum frame

FIREPLACE

Wood-burning zero-clearance fireplace

HEATING

Forced air heating system, "Weil-Mclain" gas fired high-efficiency boiler system, with Multiple zone control manifolds and thermostats.

"Wirsbo" plastic hot water piping in concrete slab

Therma-Floor gypsum topping slabs

ELECTRICAL

Typical Load Center: 125 amp main panel Wire: 12 gauge copper wire "Rom ex" Switches and receptacles: Dacora Style